

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number
WO 01/19131 A2

(51) International Patent Classification: H04R 1/00

(21) International Application Number: PCT/GB00/03398

(22) International Filing Date:
5 September 2000 (05.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
9921142.7 8 September 1999 (08.09.1999) GB(71) Applicant (for all designated States except US):
SNAP-ON EQUIPMENT LIMITED [GB/GB]; Unit 12,
Horsleys Field, Kings Lynn, Norfolk PE30 5UJ (GB).


(72) Inventor; and

(75) Inventor/Applicant (for US only): JONES, Barbara,
Lynn [GB/GB]; Snap-On Equipment Limited, Unit 12,
Horsleys Fields, Kings Lynn, Norfolk PE30 5UJ (GB).(74) Agent: ARCHER, Philip, B.; Urquhart-Dykes & Lord,
New Priestgate House, 57 Priestgate, Peterborough PE1
1JX (GB).(81) Designated States (national): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,
UG, US, UZ, VN, YU, ZA, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— Without international search report and to be republished
upon receipt of that report.For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: POSITION-DEFINING AND ENERGY-ISOLATING MOUNTINGS

(57) Abstract: A method and apparatus for mounting an acoustic emitter or detector or other sensor apparatus with respect to mount-
ing structure therefor so as to be isolated at least partially with respect thereto from the transmission of acoustic and/or electrical
energy. The mounting provides a non-elastomeric snap-together bushing formed of a plastics material which accurately positionally
locates the sensor or emitter with respect to its mounting while providing an unexpectedly high degree of isolation with respect to
transmission of acoustic and other energy forms through the mounting.

2001/19131 A2

WO 01/19131 A2